

Package ‘MultinomialCI’

September 7, 2019

License LGPL (>= 3)

Maintainer Pablo J. Villacorta <pjvi@decsai.ugr.es>

BugReports <http://decsai.ugr.es/~pjvi>

LazyData false

Title Simultaneous Confidence Intervals for Multinomial Proportions
According to the Method by Sison and Glaz

Type Package

Author Pablo J. Villacorta <pjvi@decsai.ugr.es>

Description An implementation of a method for building simultaneous confidence intervals for the probabilities of a multinomial distribution given a set of observations, proposed by Sison and Glaz in their paper:
Sison, C.P and J. Glaz. Simultaneous confidence intervals and sample size determination for multinomial proportions. Journal of the American Statistical Association, 90:366-369 (1995).
The method is an R translation of the SAS code implemented by May and Johnson in their paper:
May, W.L. and W.D. Johnson. Constructing two-sided simultaneous confidence intervals for multinomial proportions for small counts in a large number of cells. Journal of Statistical Software 5(6) (2000).
Paper and code available at <DOI:10.18637/jss.v005.i06>.

Version 1.1

URL <http://decsai.ugr.es/~pjvi>

Date 2019-09-07

Depends R (>= 2.15.0)

Collate 'aux-fn.R' 'sison.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2019-09-07 21:20:07 UTC

R topics documented:

multinomialCI 2

Index

4

multinomialCI	<i>Simultaneous Confidence Intervals for Multinomial Proportions (Sison-Graz Method)</i>
---------------	--

Description

Simultaneous confidence intervals for multinomial proportions, calculated according to the method of Sison and Graz

Usage

```
multinomialCI(x, alpha, verbose=FALSE)
```

Arguments

x	A vector of positive integers representing the number of occurrences of each class. The total number of samples equals the sum of such elements.
alpha	The significance level for the confidence intervals. Must be a real number in the interval [0, 1]
verbose	A boolean flag indicating whether details should be printed to screen during the execution of the method, or not. Nothing will be printed if the function is called only with the first two arguments.

Details

Given a vector of observations with the number of samples falling in each class of a multinomial distribution, builds the simultaneous confidence intervals for the multinomial probabilities according to the method proposed by Sison and Glaz (1995). The R code has been translated from the SAS code written by May and Johnson (2000).

Value

A $k \times 2$ real matrix, with k being the number of classes, which matches the length of the input vector x . Row i of the matrix contains the lower bound (first column) and upper bound (second column) defining the confidence interval for the probability of the i -th class, which corresponds to the i -th position of the input vector.

Author(s)

Pablo J. Villacorta Iglesias, Department of Computer Science and Artificial Intelligence, University of Granada (Spain).

<pjvi@decsai.ugr.es> - <http://decsai.ugr.es/~pjvi>

References

- Sison, C.P and J. Glaz. Simultaneous confidence intervals and sample size determination for multinomial proportions. *Journal of the American Statistical Association*, 90:366-369 (1995).
- Glaz, J. and Sison, C.P. Simultaneous confidence intervals for multinomial proportions. *Journal of Statistical Planning and Inference* 82:251-262 (1999).
- May, W.L. and W.D. Johnson. Constructing two-sided simultaneous confidence intervals for multinomial proportions for small counts in a large number of cells. *Journal of Statistical Software* 5(6) (2000). Paper and code available at <http://www.jstatsoft.org/v05/i06>.

Examples

```
# Multinomial distribution with 3 classes, from which 79 samples
# were drawn: 23 of them belong to the first class, 12 to the
# second class and 44 to the third class. Punctual estimations
# of the probabilities from this sample would be 23/79, 12/79
# and 44/79 but we want to build 95% simultaneous confidence intervals
# for the true probabilities

m = multinomialCI(c(23,12,44), 0.05);
print(paste("First class: [", m[1,1], m[1,2], "]"));
print(paste("Second class: [", m[2,1], m[2,2], "]"));
print(paste("Third class: [", m[3,1], m[3,2], "]"));
```

Index

- *Topic **confidence**
multinomialCI, 2
 - *Topic **estimation**
multinomialCI, 2
 - *Topic **interval**
multinomialCI, 2
 - *Topic **multinomial**
multinomialCI, 2
- multinomialCI, 2