

**NAME**

**t1unmac** – translate a Mac PostScript Type 1 font into PFA or PFB format

**SYNOPSIS**

**t1unmac** [**-a|-b**] [**-r**] [*input* [*output*]]

**DESCRIPTION**

**t1unmac** extracts POST resources from a Macintosh PostScript font file and creates a PFA (hexadecimal) or PFB (binary) font file. The file *input* should be in MacBinary I or II, AppleSingle, AppleDouble, or Bin-Hex format, or it can be a raw resource fork. If the file is a raw resource fork, you need to give the ‘**--raw**’ option; otherwise **t1unmac** should automatically figure out what kind of file you have. If the file *output* is not specified output goes to the standard output.

**OPTIONS**

**--pfa, -a**

Output in PFA (ASCII) format.

**--pfb, -b**

Output in PFB (binary) format. This is the default.

**--raw, -r**

Indicates that the input is a raw resource fork.

**--macbinary**

Indicates that the input is in MacBinary I or II format.

**--applesingle**

Indicates that the input is in AppleSingle format.

**--appledouble**

Indicates that the input is in AppleDouble format.

**--binhex**

Indicates that the input is in BinHex 4.0 format.

**--block-length=num, -l num**

PFB only: Set the maximum output block length to *num*. The default length is as large as memory allows.

**--line-length=num, -l num**

PFA only: Set the maximum length of encrypted lines in the output to *num*. (These are the lines consisting wholly of hexadecimal digits.) The default is 64.

**EXAMPLES**

On Mac OS X, you can use **t1unmac** to translate a font into PFA or PFB format as follows:

```
% t1unmac --raw FONTPATH/..namedfork/rsrc > OUTPUT
```

**SEE ALSO**

**t1mac(1), t1ascii(1), t1binary(1), t1asm(1), t1disasm(1)**

**AUTHORS**

Lee Hetherington (ilh@lcs.mit.edu)

Eddie Kohler (ekohler@gmail.com)

Ported to Microsoft C/C++ Compiler and MS-DOS operating system by Kai-Uwe Herbing (herbing@netmbx.netmbx.de).