

Array operations in the gRbase package

Søren Højsgaard

gRbase version 2.0.2 as of 2024-05-29

Contents

1	Introduction	2
2	Arrays/tables in R	2
2.1	Cross classified data - contingency tables	2
2.2	Defining arrays	3
3	Operations on arrays	4
3.1	Normalizing an array	4
3.2	Subsetting an array – slicing	4
3.3	Collapsing and inflating arrays	5
3.4	Permuting an array	6
3.5	Equality	7
3.6	Aligning	7
3.7	Multiplication, addition etc: +, −, *, /	8
3.8	An array as a probability density	9
3.9	Miscellaneous	9
4	Examples	10
4.1	A Bayesian network	10
4.2	Iterative Proportional Scaling (IPS)	11
5	Some low level functions	12
5.1	cell2entry(), entry2cell() and next_cell()	13
5.2	next_cell_slice() and slice2entry()	14
5.3	fact_grid() – Factorial grid	14
A	More about slicing	15

```
## Warning: package 'gRbase' was built under R version 4.4.0
## Error: package or namespace load failed for 'gRbase' in dyn.load(file, DLLpath = DLLpath,
...):
```

```
## unable to load shared object '/home/sorenh/R/x86_64-pc-linux-gnu-library/4.3/gRbase/libs/gRbase.so':  
## libRblas.so: cannot open shared object file: No such file or directory
```

1 Introduction

This note describes some operations on arrays in R. These operations have been implemented to facilitate implementation of graphical models and Bayesian networks in R.

2 Arrays/tables in R

The documentation of R states the following about arrays:

An array in R can have one, two or more dimensions. It is simply a vector which is stored with additional attributes giving the dimensions (attribute "dim") and optionally names for those dimensions (attribute "dimnames"). A two-dimensional array is the same thing as a matrix. One-dimensional arrays often look like vectors, but may be handled differently by some functions.

2.1 Cross classified data - contingency tables

Arrays appear for example in connection with cross classified data. The array `hec` below is an excerpt of the `HairEyeColor` array in R:

```
hec <- c(32, 53, 11, 50, 10, 25, 36, 66, 9, 34, 5, 29)  
dim(hec) <- c(2, 3, 2)  
dimnames(hec) <- list(Hair = c("Black", "Brown"),  
                      Eye = c("Brown", "Blue", "Hazel"),  
                      Sex = c("Male", "Female"))  
  
hec  
## , , Sex = Male  
##  
##      Eye  
## Hair   Brown Blue Hazel  
## Black   32   11   10  
## Brown   53   50   25  
##  
## , , Sex = Female  
##  
##      Eye  
## Hair   Brown Blue Hazel  
## Black   36    9    5  
## Brown   66   34   29
```

Above, `hec` is an array because it has a `dim` attribute. Moreover, `hec` also has a `dimnames` attribute naming the levels of each dimension. Notice that each dimension is given a name.

Printing arrays can take up a lot of space. Alternative views on an array can be obtained with `ftable()` or by converting the array to a dataframe with `as.data.frame.table()`. We shall do so in the following.

```
##flat <- function(x) {ftable(x, row.vars=1)}
flat <- function(x, n=4) {as.data.frame.table(x) %>% head(n)}
hec %>% flat
```

```
## Error in hec %>% flat: could not find function "%>%"
```

An array with named dimensions is in this package called a *named array*. The functionality described below relies heavily on arrays having named dimensions. A check for an object being a named array is provided by `is.named.array()`^[gRbase]

```
is.named.array(hec)
```

```
## Error in is.named.array(hec): could not find function "is.named.array"
```

2.2 Defining arrays

Another way is to use `tabNew()`^[gRbase] from `gRbase`. This function is flexible wrt the input; for example:

```
dn <- list(Hair=c("Black", "Brown"), Eye=~Brown:Blue:Hazel, Sex=~Male:Female)
counts <- c(32, 53, 11, 50, 10, 25, 36, 66, 9, 34, 5, 29)
z3 <- tabNew(~Hair:Eye:Sex, levels=dn, value=counts)
```

```
## Error in tabNew(~Hair:Eye:Sex, levels = dn, value = counts): could not find function "tabNew"
```

```
z4 <- tabNew(c("Hair", "Eye", "Sex"), levels=dn, values=counts)
```

```
## Error in tabNew(c("Hair", "Eye", "Sex"), levels = dn, values = counts): could not find function "tabNew"
```

Notice that the levels list (`dn` above) when used in `tabNew()`^[gRbase] is allowed to contain superfluous elements. Default `dimnames` are generated with

```
z5 <- tabNew(~Hair:Eye:Sex, levels=c(2, 3, 2), values = counts)
```

```
## Error in tabNew(~Hair:Eye:Sex, levels = c(2, 3, 2), values = counts): could not find function "tabNew"
```

```
dimnames(z5) %>% str
```

```
## Error in dimnames(z5) %>% str: could not find function "%>%"
```

Using `tabNew`^[gRbase], arrays can be normalized to sum to one in two ways: 1) Normalization can be over the first variable for *each* configuration of all other variables and 2) over all configurations. For example:

```
z6 <- tabNew(~Hair:Eye:Sex, levels=c(2, 3, 2), values=counts, normalize="first")
```

```
## Error in tabNew(~Hair:Eye:Sex, levels = c(2, 3, 2), values = counts, normalize = "first"): could not find function "tabNew"
```

```
z6 %>% flat
```

```
## Error in z6 %>% flat: could not find function "%>%"
```

3 Operations on arrays

In the following we shall denote the dimnames (or variables) of the array `hec` by H , E and S and we let (h, e, s) denote a configuration of these variables. The contingency table above shall be denoted by T_{HES} and we shall refer to the (h, e, s) -entry of T_{HES} as $T_{HES}(h, e, s)$.

3.1 Normalizing an array

Normalize an array with `tabNormalize()`_[gRbase] Entries of an array can be normalized to sum to one in two ways: 1) Normalization can be over the first variable for *each* configuration of all other variables and 2) over all configurations. For example:

```
tabNormalize(z5, "first") %>% flat
## Error in tabNormalize(z5, "first") %>% flat: could not find function "%>%"
```

3.2 Subsetting an array – slicing

We can subset arrays (this will also be called “slicing”) in different ways. Notice that the result is not necessarily an array. Slicing can be done using standard R code or using `tabSlice`_[gRbase]. The virtue of `tabSlice`_[gRbase] comes from the flexibility when specifying the slice:

The following leads from the original $2 \times 3 \times 2$ array to a 2×2 array by cutting away the `Sex=Male` and `Eye=Brown` slice of the array:

```
tabSlice(hec, slice=list(Eye=c("Blue", "Hazel"), Sex="Female"))
## Error in tabSlice(hec, slice = list(Eye = c("Blue", "Hazel"), Sex = "Female")): could not find function "tabSlice"
## Notice: levels can be written as numerics
## tabSlice(hec, slice=list(Eye=2:3, Sex="Female"))
```

We may also regard the result above as a $2 \times 2 \times 1$ array:

```
tabSlice(hec, slice=list(Eye=c("Blue", "Hazel"), Sex="Female"), drop=FALSE)
## Error in tabSlice(hec, slice = list(Eye = c("Blue", "Hazel"), Sex = "Female"), : could not find function "tabSlice"
```

If slicing leads to a one dimensional array, the output will by default not be an array but a vector (without a `dim` attribute). However, the result can be forced to be a 1-dimensional array:

```
## A vector:
t1 <- tabSlice(hec, slice=list(Hair=1, Sex="Female")); t1
## Error in tabSlice(hec, slice = list(Hair = 1, Sex = "Female")): could not find function "tabSlice"
## Error in eval(expr, envir, enclos): object 't1' not found
## A 1-dimensional array:
t2 <- tabSlice(hec, slice=list(Hair=1, Sex="Female"), as.array=TRUE); t2
```

```
## Error in tabSlice(hec, slice = list(Hair = 1, Sex = "Female"), as.array = TRUE): could not
find function "tabSlice"

## Error in eval(expr, envir, enclos): object 't2' not found

## A higher dimensional array (in which some dimensions only have one level)
t3 <- tabSlice(hec, slice=list(Hair=1, Sex="Female"), drop=FALSE); t3

## Error in tabSlice(hec, slice = list(Hair = 1, Sex = "Female"), drop = FALSE): could not
find function "tabSlice"

## Error in eval(expr, envir, enclos): object 't3' not found
```

The difference between the last two forms can be clarified:

```
t2 %>% flat

## Error in t2 %>% flat: could not find function "%>%"

t3 %>% flat

## Error in t3 %>% flat: could not find function "%>%"
```

3.3 Collapsing and inflating arrays

Collapsing: The HE -marginal array T_{HE} of T_{HES} is the array with values

$$T_{HE}(h, e) = \sum_s T_{HES}(h, e, s)$$

Inflating: The “opposite” operation is to extend an array. For example, we can extend T_{HE} to have a third dimension, e.g. \mathbf{Sex} . That is

$$\tilde{T}_{SHE}(s, h, e) = T_{HE}(h, e)$$

so $\tilde{T}_{SHE}(s, h, e)$ is constant as a function of s .

With `gRbase` we can collapse arrays with¹:

```
he <- tabMarg(hec, c("Hair", "Eye"))

## Error in tabMarg(hec, c("Hair", "Eye")): could not find function "tabMarg"

he

## Error in eval(expr, envir, enclos): object 'he' not found
```

```
## Alternatives
tabMarg(hec, ~Hair:Eye)

## Error in tabMarg(hec, ~Hair:Eye): could not find function "tabMarg"

tabMarg(hec, c(1, 2))
```

¹FIXME: Should allow for abbreviations in formula and character vector specifications.

```
## Error in tabMarg(hec, c(1, 2)): could not find function "tabMarg"
```

```
hec %a_% ~Hair:Eye
```

```
## Error in hec %a_% ~Hair:Eye: could not find function "%a_%"
```

Notice that collapsing is a projection in the sense that applying the operation again does not change anything:

```
he1 <- tabMarg(hec, c("Hair", "Eye"))
```

```
## Error in tabMarg(hec, c("Hair", "Eye")): could not find function "tabMarg"
```

```
he2 <- tabMarg(he1, c("Hair", "Eye"))
```

```
## Error in tabMarg(he1, c("Hair", "Eye")): could not find function "tabMarg"
```

```
tabEqual(he1, he2)
```

```
## Error in tabEqual(he1, he2): could not find function "tabEqual"
```

Expand an array by adding additional dimensions with `tabExpand()`_[gRbase]:

```
extra.dim <- list(Sex=c("Male", "Female"))  
tabExpand(he, extra.dim)
```

```
## Error in tabExpand(he, extra.dim): could not find function "tabExpand"
```

```
## Alternatives
```

```
he %a^% extra.dim
```

```
## Error in he %a^% extra.dim: could not find function "%a^%"
```

Notice that expanding and collapsing brings us back to where we started:

```
(he %a^% extra.dim) %a_% c("Hair", "Eye")
```

```
## Error in (he %a^% extra.dim) %a_% c("Hair", "Eye"): could not find function "%a_%"
```

3.4 Permuting an array

A reorganization of the table can be made with `tabPerm`_[gRbase] (similar to `aperm()`), but `tabPerm`_[gRbase] allows for a formula and for variable abbreviation:

```
tabPerm(hec, ~Eye:Sex:Hair) %>% flat
```

```
## Error in tabPerm(hec, ~Eye:Sex:Hair) %>% flat: could not find function "%>%"
```

Alternative forms (the first two also works for `aperm`):

```

tabPerm(hec, c("Eye", "Sex", "Hair"))

## Error in tabPerm(hec, c("Eye", "Sex", "Hair")): could not find function "tabPerm"

tabPerm(hec, c(2, 3, 1))

## Error in tabPerm(hec, c(2, 3, 1)): could not find function "tabPerm"

tabPerm(hec, ~Ey:Se:Ha)

## Error in tabPerm(hec, ~Ey:Se:Ha): could not find function "tabPerm"

tabPerm(hec, c("Ey", "Se", "Ha"))

## Error in tabPerm(hec, c("Ey", "Se", "Ha")): could not find function "tabPerm"

```

3.5 Equality

Two arrays are defined to be identical 1) if they have the same dimnames and 2) if, possibly after a permutation, all values are identical (up to a small numerical difference):

```

hec2 <- tabPerm(hec, 3:1)

## Error in tabPerm(hec, 3:1): could not find function "tabPerm"

tabEqual(hec, hec2)

## Error in tabEqual(hec, hec2): could not find function "tabEqual"

```

```

## Alternative
hec %a==% hec2

## Error in hec %a==% hec2: could not find function "%a==%"

```

3.6 Aligning

We can align one array according to the ordering of another:

```

hec2 <- tabPerm(hec, 3:1)

## Error in tabPerm(hec, 3:1): could not find function "tabPerm"

tabAlign(hec2, hec)

## Error in tabAlign(hec2, hec): could not find function "tabAlign"

```

```

## Alternative:
tabAlign(hec2, dimnames(hec))

## Error in tabAlign(hec2, dimnames(hec)): could not find function "tabAlign"

```

3.7 Multiplication, addition etc: +, -, *, /

The product of two arrays T_{HE} and T_{HS} is defined to be the array \tilde{T}_{HES} with entries

$$\tilde{T}_{HES}(h, e, s) = T_{HE}(h, e) + T_{HS}(h, s)$$

The sum, difference and quotient is defined similarly: This is done with `tabProd()[gRbase]`, `tabAdd()[gRbase]`, `tabDiff()[gRbase]` and `tabDiv()[gRbase]`:

```
hs <- tabMarg(hec, ~Hair:Eye)

## Error in tabMarg(hec, ~Hair:Eye): could not find function "tabMarg"

tabMult(he, hs)

## Error in tabMult(he, hs): could not find function "tabMult"
```

Available operations:

```
tabAdd(he, hs)

## Error in tabAdd(he, hs): could not find function "tabAdd"

tabSubt(he, hs)

## Error in tabSubt(he, hs): could not find function "tabSubt"

tabMult(he, hs)

## Error in tabMult(he, hs): could not find function "tabMult"

tabDiv(he, hs)

## Error in tabDiv(he, hs): could not find function "tabDiv"

tabDiv0(he, hs) ## Convention 0/0 = 0

## Error in tabDiv0(he, hs): could not find function "tabDiv0"
```

Shortcuts:

```
## Alternative
he %a+% hs

## Error in he %a+% hs: could not find function "%a+%"

he %a-% hs

## Error in he %a-% hs: could not find function "%a-%%"

he %a*% hs

## Error in he %a*% hs: could not find function "%a*%"
```

```

he %a/% hs

## Error in he %a/% hs: could not find function "%a/%"

he %a/0% hs ## Convention 0/0 = 0

## Error in he %a/0% hs: could not find function "%a/0%"

```

Multiplication and addition of (a list of) multiple arrays is accomplished with `tabProd()`_[gRbase] and `tabSum()`_[gRbase] (much like `prod()`_[gRbase] and `sum()`_[gRbase]):

```

es <- tabMarg(hec, ~Eye:Sex)

## Error in tabMarg(hec, ~Eye:Sex): could not find function "tabMarg"

tabSum(he, hs, es)

## Error in tabSum(he, hs, es): could not find function "tabSum"

## tabSum(list(he, hs, es))

```

3.8 An array as a probability density

If an array consists of non-negative numbers then it may be regarded as an (unnormalized) discrete multivariate density. With this view, the following examples should be self explanatory:

```

tabDist(hec, marg=~Hair:Eye)

## Error in tabDist(hec, marg = ~Hair:Eye): could not find function "tabDist"

tabDist(hec, cond=~Sex)

## Error in tabDist(hec, cond = ~Sex): could not find function "tabDist"

tabDist(hec, marg=~Hair, cond=~Sex)

## Error in tabDist(hec, marg = ~Hair, cond = ~Sex): could not find function "tabDist"

```

3.9 Miscellaneous

Multiply values in a slice by some number and all other values by another number:

```

tabSliceMult(es, list(Sex="Female"), val=10, comp=0)

## Error in tabSliceMult(es, list(Sex = "Female"), val = 10, comp = 0): could not find function
"tabSliceMult"

```

4 Examples

4.1 A Bayesian network

A classical example of a Bayesian network is the “sprinkler example”, see e.g. http://en.wikipedia.org/wiki/Bayesian_network:

Suppose that there are two events which could cause grass to be wet: either the sprinkler is on or it is raining. Also, suppose that the rain has a direct effect on the use of the sprinkler (namely that when it rains, the sprinkler is usually not turned on). Then the situation can be modeled with a Bayesian network.

We specify conditional probabilities $p(r)$, $p(s|r)$ and $p(w|s,r)$ as follows (notice that the vertical conditioning bar ($|$) is replaced by the horizontal underscore:

```
yn <- c("y", "n")
lev <- list(rain=yn, sprinkler=yn, wet=yn)
r <- tabNew(~rain, levels=lev, values=c(.2, .8))

## Error in tabNew(~rain, levels = lev, values = c(0.2, 0.8)): could not find function "tabNew"

s_r <- tabNew(~sprinkler:rain, levels = lev, values = c(.01, .99, .4, .6))

## Error in tabNew(~sprinkler:rain, levels = lev, values = c(0.01, 0.99, : could not find
function "tabNew"

w_sr <- tabNew( ~wet:sprinkler:rain, levels=lev,
               values=c(.99, .01, .8, .2, .9, .1, 0, 1))

## Error in tabNew(~wet:sprinkler:rain, levels = lev, values = c(0.99, 0.01, : could not find
function "tabNew"

r

## Error in eval(expr, envir, enclos): object 'r' not found

s_r %>% flat

## Error in s_r %>% flat: could not find function "%>%"

w_sr %>% flat

## Error in w_sr %>% flat: could not find function "%>%"
```

The joint distribution $p(r, s, w) = p(r)p(s|r)p(w|s, r)$ can be obtained with `tabProd()`_[gRbase] ways:

```
joint <- tabProd(r, s_r, w_sr); joint %>% flat

## Error in tabProd(r, s_r, w_sr): could not find function "tabProd"
## Error in joint %>% flat: could not find function "%>%"
```

What is the probability that it rains given that the grass is wet? We find $p(r, w) = \sum_s p(r, s, w)$ and then $p(r|w) = p(r, w)/p(w)$. Can be done in various ways: with `tabDist()`_[gRbase]

```
tabDist(joint, marg=~rain, cond=~wet)

## Error in tabDist(joint, marg = ~rain, cond = ~wet): could not find function "tabDist"
```

```
## Alternative:
rw <- tabMarg(joint, ~rain + wet)

## Error in tabMarg(joint, ~rain + wet): could not find function "tabMarg"

tabDiv(rw, tabMarg(rw, ~wet))

## Error in tabDiv(rw, tabMarg(rw, ~wet)): could not find function "tabDiv"

## or
rw %a/% (rw %a_% ~wet)

## Error in rw %a/% (rw %a_% ~wet): could not find function "%a/%"
```

```
## Alternative:
x <- tabSliceMult(rw, slice=list(wet="y")); x

## Error in tabSliceMult(rw, slice = list(wet = "y")): could not find function "tabSliceMult"
## Error in eval(expr, envir, enclos): object 'x' not found

tabDist(x, marg=~rain)

## Error in tabDist(x, marg = ~rain): could not find function "tabDist"
```

4.2 Iterative Proportional Scaling (IPS)

We consider the 3-way lizard data from gRbase:

```
data(lizard, package="gRbase")
lizard %>% flat

## Error in lizard %>% flat: could not find function "%>%"
```

Consider the two factor log-linear model for the `lizard` data. Under the model the expected counts have the form

$$\log m(d, h, s) = a_1(d, h) + a_2(d, s) + a_3(h, s)$$

If we let $n(d, h, s)$ denote the observed counts, the likelihood equations are: Find $m(d, h, s)$ such that

$$m(d, h) = n(d, h), \quad m(d, s) = n(d, s), \quad m(h, s) = n(h, s)$$

where $m(d, h) = \sum_s m(d, h, s)$ etc. The updates are as follows: For the first term we have

$$m(d, h, s) \leftarrow m(d, h, s) \frac{n(d, h)}{m(d, h)}$$

After iterating the updates will not change and we will have equality: $m(d, h, s) = m(d, h, s) \frac{n(d, h)}{m(d, h)}$ and summing over s shows that the equation $m(d, h) = n(d, h)$ is satisfied.

A rudimentary implementation of iterative proportional scaling for log-linear models is straight forward:

```
myips <- function(indata, glist){
  fit <- indata
  fit[] <- 1
  ## List of sufficient marginal tables
  md <- lapply(glist, function(g) tabMarg(indata, g))

  for (i in 1:4){
    for (j in seq_along(glist)){
      mf <- tabMarg(fit, glist[[j]])
      # adj <- tabDiv( md[[ j ]], mf)
      # fit <- tabMult( fit, adj )
      ## or
      adj <- md[[ j ]] %a/% mf
      fit <- fit %a*% adj
    }
  }
  pearson <- sum((fit - indata)^2 / fit)
  list(pearson=pearson, fit=fit)
}

glist <- list(c("species", "diam"),c("species", "height"),c("diam", "height"))

fm1 <- myips(lizard, glist)

## Error in tabMarg(indata, g): could not find function "tabMarg"

fm1$pearson

## Error in eval(expr, envir, enclos): object 'fm1' not found

fm1$fit %>% flat

## Error in fm1$fit %>% flat: could not find function "%>%"

fm2 <- loglin(lizard, glist, fit=T)
## 4 iterations: deviation 0.009619

fm2$pearson
## [1] 0.1506

fm2$fit %>% flat

## Error in fm2$fit %>% flat: could not find function "%>%"
```

5 Some low level functions

For e.g. a $2 \times 3 \times 2$ array, the entries are such that the first variable varies fastest so the ordering of the cells are (1, 1, 1), (2, 1, 1), (1, 2, 1), (2, 2, 1), (1, 3, 1) and so on. To find the value of such a

cell, say, (j, k, l) in the array (which is really just a vector), the cell is mapped into an entry of a vector.

For example, cell $(2, 3, 1)$ (Hair=Brown, Eye=Hazel, Sex=Male) must be mapped to entry 4 in

```
hec
## , , Sex = Male
##
##      Eye
## Hair   Brown Blue Hazel
## Black   32   11   10
## Brown   53   50   25
##
## , , Sex = Female
##
##      Eye
## Hair   Brown Blue Hazel
## Black   36    9    5
## Brown   66   34   29

c(hec)
## [1] 32 53 11 50 10 25 36 66  9 34  5 29
```

For illustration we do:

```
cell2name <- function(cell, dimnames){
  unlist(lapply(1:length(cell), function(m) dimnames[[m]][cell[m]]))
}
cell2name(c(2,3,1), dimnames(hec))
## [1] "Brown" "Hazel" "Male"
```

5.1 cell2entry(), entry2cell() and next_cell()

The map from a cell to the corresponding entry is provided by `cell2entry()`_[gRbase]. The reverse operation, going from an entry to a cell (which is much less needed) is provided by `entry2cell()`_[gRbase].

```
cell2entry(c(2,3,1), dim=c(2, 3, 2))

## Error in cell2entry(c(2, 3, 1), dim = c(2, 3, 2)): could not find function "cell2entry"

entry2cell(6, dim=c(2, 3, 2))

## Error in entry2cell(6, dim = c(2, 3, 2)): could not find function "entry2cell"
```

Given a cell, say $i = (2, 3, 1)$ in a $2 \times 3 \times 2$ array we often want to find the next cell in the table following the convention that the first factor varies fastest, that is $(1, 1, 2)$. This is provided by `next_cell()`_[gRbase].

```
next_cell(c(2,3,1), dim=c(2, 3, 2))

## Error in next_cell(c(2, 3, 1), dim = c(2, 3, 2)): could not find function "next_cell"
```

5.2 next_cell_slice() and slice2entry()

Given that we look at cells for which the index in dimension 2 is at level 3 (that is Eye=Hazel), i.e. cells of the form $(j, 3, l)$. Given such a cell, what is then the next cell that also satisfies this constraint. This is provided by `next_cell_slice()`²_[gRbase].

```
next_cell_slice(c(1,3,1), slice_marg=2, dim=c( 2, 3, 2 ))

## Error in next_cell_slice(c(1, 3, 1), slice_marg = 2, dim = c(2, 3, 2)): could not find
function "next_cell_slice"

next_cell_slice(c(2,3,1), slice_marg=2, dim=c( 2, 3, 2 ))

## Error in next_cell_slice(c(2, 3, 1), slice_marg = 2, dim = c(2, 3, 2)): could not find
function "next_cell_slice"
```

Given that in dimension 2 we look at level 3. We want to find entries for the cells of the form $(j, 3, l)$.³

```
slice2entry(slice_cell=3, slice_marg=2, dim=c( 2, 3, 2 ))

## Error in slice2entry(slice_cell = 3, slice_marg = 2, dim = c(2, 3, 2)): could not find
function "slice2entry"
```

To verify that we indeed get the right cells:

```
r <- slice2entry(slice_cell=3, slice_marg=2, dim=c( 2, 3, 2 ))

## Error in slice2entry(slice_cell = 3, slice_marg = 2, dim = c(2, 3, 2)): could not find
function "slice2entry"

lapply(lapply(r, entry2cell, c( 2, 3, 2 )),
       cell2name, dimnames(hec))

## Error in eval(expr, envir, enclos): object 'entry2cell' not found
```

5.3 fact_grid() – Factorial grid

Using the operations above we can obtain the combinations of the factors as a matrix:

```
head( fact_grid( c(2, 3, 2) ), 6 )

## Error in fact_grid(c(2, 3, 2)): could not find function "fact_grid"
```

A similar dataframe can also be obtained with the standard R function `expand.grid` (but `factGrid` is faster)

```
head( expand.grid(list(1:2, 1:3, 1:2)), 6 )
```

²FIXME: sliceset should be called margin.

³FIXME:slice2cell and sliceset should be renamed

```
##   Var1 Var2 Var3
## 1   1   1   1
## 2   2   1   1
## 3   1   2   1
## 4   2   2   1
## 5   1   3   1
## 6   2   3   1
```

A More about slicing

Slicing using standard R code can be done as follows:

```
hec[, 2:3, ] %>% flat ## A 2 x 2 x 2 array

## Error in hec[, 2:3, ] %>% flat: could not find function "%>%"

hec[1, , 1] ## A vector
## Brown Blue Hazel
## 32 11 10

hec[1, , 1, drop=FALSE] ## A 1 x 3 x 1 array
## , , Sex = Male
##
## Eye
## Hair Brown Blue Hazel
## Black 32 11 10
```

Programmatically we can do the above as

```
do.call("[", c(list(hec), list(TRUE, 2:3, TRUE))) %>% flat

## Error in do.call("[", c(list(hec), list(TRUE, 2:3, TRUE))) %>% flat: could not find function "%>%"

do.call("[", c(list(hec), list(1, TRUE, 1)))
do.call("[", c(list(hec), list(1, TRUE, 1), drop=FALSE))
```

gRbase provides two alternatives for each of these three cases above:

```
tabSlicePrim(hec, slice=list(TRUE, 2:3, TRUE)) %>% flat

## Error in tabSlicePrim(hec, slice = list(TRUE, 2:3, TRUE)) %>% flat: could not find function "%>%"

tabSlice(hec, slice=list(c(2, 3)), margin=2) %>% flat

## Error in tabSlice(hec, slice = list(c(2, 3)), margin = 2) %>% flat: could not find function "%>%"

tabSlicePrim(hec, slice=list(1, TRUE, 1))

## Error in tabSlicePrim(hec, slice = list(1, TRUE, 1)): could not find function "tabSlicePrim"
```

```
tabSlice(hec, slice=list(1, 1), margin=c(1, 3))

## Error in tabSlice(hec, slice = list(1, 1), margin = c(1, 3)): could not find function "tabSlice"

tabSlicePrim(hec, slice=list(1, TRUE, 1), drop=FALSE)

## Error in tabSlicePrim(hec, slice = list(1, TRUE, 1), drop = FALSE): could not find function
"tabSlicePrim"

tabSlice(hec, slice=list(1, 1), margin=c(1, 3), drop=FALSE)

## Error in tabSlice(hec, slice = list(1, 1), margin = c(1, 3), drop = FALSE): could not find
function "tabSlice"
```