

NAME

`cjpeg` – compress an image file to a JPEG file

SYNOPSIS

`cjpeg` [*options*] [*filename*]

DESCRIPTION

`cjpeg` compresses the named image file, or the standard input if no file is named, and produces a JPEG/JFIF file on the standard output. The currently supported input file formats are: PPM (PBMPLUS color format), PGM (PBMPLUS gray-scale format), BMP, Targa, and RLE (Utah Raster Toolkit format). (RLE is supported only if the URT library is available.)

OPTIONS

All switch names may be abbreviated; for example, `-grayscale` may be written `-gray` or `-gr`. Most of the "basic" switches can be abbreviated to as little as one letter. Upper and lower case are equivalent (thus `-BMP` is the same as `-bmp`). British spellings are also accepted (e.g., `-greyscale`), though for brevity these are not mentioned below.

The basic switches are:

`-quality` *N*[*,...*]

Scale quantization tables to adjust image quality. Quality is 0 (worst) to 100 (best); default is 75. (See below for more info.)

`-grayscale`

Create monochrome JPEG file from color input. Be sure to use this switch when compressing a grayscale BMP file, because `cjpeg` isn't bright enough to notice whether a BMP file uses only shades of gray. By saying `-grayscale`, you'll get a smaller JPEG file that takes less time to process.

`-rgb` Create RGB JPEG file. Using this switch suppresses the conversion from RGB colorspace input to the default YCbCr JPEG colorspace. Use this switch in combination with the `-block` *N* switch (see below) for lossless JPEG coding.

`-optimize`

Perform optimization of entropy encoding parameters. Without this, default encoding parameters are used. `-optimize` usually makes the JPEG file a little smaller, but `cjpeg` runs somewhat slower and needs much more memory. Image quality and speed of decompression are unaffected by `-optimize`.

`-progressive`

Create progressive JPEG file (see below).

`-scale` *M/N*

Scale the output image by a factor *M/N*. Currently supported scale factors are *M/N* with all *N* from 1 to 16, where *M* is the destination DCT size, which is 8 by default (see `-block` *N* switch below).

`-targa` Input file is Targa format. Targa files that contain an "identification" field will not be automatically recognized by `cjpeg`; for such files you must specify `-targa` to make `cjpeg` treat the input as Targa format. For most Targa files, you won't need this switch.

The `-quality` switch lets you trade off compressed file size against quality of the reconstructed image: the higher the quality setting, the larger the JPEG file, and the closer the output image will be to the original input. Normally you want to use the lowest quality setting (smallest file) that decompresses into something visually indistinguishable from the original image. For this purpose the quality setting should be between 50 and 95; the default of 75 is often about right. If you see defects at `-quality` 75, then go up 5 or 10 counts at a time until you are happy with the output image. (The optimal setting will vary from one image to another.)

`-quality` 100 will generate a quantization table of all 1's, minimizing loss in the quantization step (but there is still information loss in subsampling, as well as roundoff error). This setting is mainly of interest for

experimental purposes. Quality values above about 95 are **not** recommended for normal use; the compressed file size goes up dramatically for hardly any gain in output image quality.

In the other direction, quality values below 50 will produce very small files of low image quality. Settings around 5 to 10 might be useful in preparing an index of a large image library, for example. Try **-quality 2** (or so) for some amusing Cubist effects. (Note: quality values below about 25 generate 2-byte quantization tables, which are considered optional in the JPEG standard. **cjpeg** emits a warning message when you give such a quality value, because some other JPEG programs may be unable to decode the resulting file. Use **-baseline** if you need to ensure compatibility at low quality values.)

The **-quality** option has been extended in IJG version 7 for support of separate quality settings for luminance and chrominance (or in general, for every provided quantization table slot). This feature is useful for high-quality applications which cannot accept the damage of color data by coarse subsampling settings. You can now easily reduce the color data amount more smoothly with finer control without separate subsampling. The resulting file is fully compliant with standard JPEG decoders. Note that the **-quality** ratings refer to the quantization table slots, and that the last value is replicated if there are more q-table slots than parameters. The default q-table slots are 0 for luminance and 1 for chrominance with default tables as given in the JPEG standard. This is compatible with the old behaviour in case that only one parameter is given, which is then used for both luminance and chrominance (slots 0 and 1). More or custom quantization tables can be set with **-qtables** and assigned to components with **-qslots** parameter (see the "wizard" switches below). **Caution:** You must explicitly add **-sample 1x1** for efficient separate color quality selection, since the default value used by library is 2x2!

The **-progressive** switch creates a "progressive JPEG" file. In this type of JPEG file, the data is stored in multiple scans of increasing quality. If the file is being transmitted over a slow communications link, the decoder can use the first scan to display a low-quality image very quickly, and can then improve the display with each subsequent scan. The final image is exactly equivalent to a standard JPEG file of the same quality setting, and the total file size is about the same --- often a little smaller.

Switches for advanced users:

-arithmetic

Use arithmetic coding. **Caution:** arithmetic coded JPEG is not yet widely implemented, so many decoders will be unable to view an arithmetic coded JPEG file at all.

-block N

Set DCT block size. All N from 1 to 16 are possible. Default is 8 (baseline format). Larger values produce higher compression, smaller values produce higher quality (exact DCT stage possible with 1 or 2; with the default quality of 75 and default Luminance qtable the DCT+Quantization stage is lossless for N=1). **Caution:** An implementation of the JPEG SmartScale extension is required for this feature. SmartScale enabled JPEG is not yet widely implemented, so many decoders will be unable to view a SmartScale extended JPEG file at all.

-dct int

Use integer DCT method (default).

-dct fast

Use fast integer DCT (less accurate).

-dct float

Use floating-point DCT method. The float method is very slightly more accurate than the int method, but is much slower unless your machine has very fast floating-point hardware. Also note that results of the floating-point method may vary slightly across machines, while the integer methods should give the same results everywhere. The fast integer method is much less accurate than the other two.

-nosmooth

Don't use high-quality downsampling.

-restart *N*

Emit a JPEG restart marker every *N* MCU rows, or every *N* MCU blocks if "B" is attached to the number. **-restart 0** (the default) means no restart markers.

-smooth *N*

Smooth the input image to eliminate dithering noise. *N*, ranging from 1 to 100, indicates the strength of smoothing. 0 (the default) means no smoothing.

-maxmemory *N*

Set limit for amount of memory to use in processing large images. Value is in thousands of bytes, or millions of bytes if "M" is attached to the number. For example, **-max 4m** selects 4000000 bytes. If more space is needed, temporary files will be used.

-outfile *name*

Send output image to the named file, not to standard output.

-verbose

Enable debug printout. More **-v**'s give more output. Also, version information is printed at startup.

-debug

Same as **-verbose**.

The **-restart** option inserts extra markers that allow a JPEG decoder to resynchronize after a transmission error. Without restart markers, any damage to a compressed file will usually ruin the image from the point of the error to the end of the image; with restart markers, the damage is usually confined to the portion of the image up to the next restart marker. Of course, the restart markers occupy extra space. We recommend **-restart 1** for images that will be transmitted across unreliable networks such as Usenet.

The **-smooth** option filters the input to eliminate fine-scale noise. This is often useful when converting dithered images to JPEG: a moderate smoothing factor of 10 to 50 gets rid of dithering patterns in the input file, resulting in a smaller JPEG file and a better-looking image. Too large a smoothing factor will visibly blur the image, however.

Switches for wizards:

-baseline

Force baseline-compatible quantization tables to be generated. This clamps quantization values to 8 bits even at low quality settings. (This switch is poorly named, since it does not ensure that the output is actually baseline JPEG. For example, you can use **-baseline** and **-progressive** together.)

-qtables *file*

Use the quantization tables given in the specified text file.

-qslots *N[,...]*

Select which quantization table to use for each color component.

-sample *HxV[,...]*

Set JPEG sampling factors for each color component.

-scans *file*

Use the scan script given in the specified text file.

The "wizard" switches are intended for experimentation with JPEG. If you don't know what you are doing, **don't use them**. These switches are documented further in the file wizard.txt.

EXAMPLES

This example compresses the PPM file foo.ppm with a quality factor of 60 and saves the output as foo.jpg:

```
cjpeg -quality 60 foo.ppm > foo.jpg
```

HINTS

Color GIF files are not the ideal input for JPEG; JPEG is really intended for compressing full-color (24-bit) images. In particular, don't try to convert cartoons, line drawings, and other images that have only a few distinct colors. GIF works great on these, JPEG does not. If you want to convert a GIF to JPEG, you

should experiment with **cjpeg**'s **-quality** and **-smooth** options to get a satisfactory conversion. **-smooth 10** or so is often helpful.

Avoid running an image through a series of JPEG compression/decompression cycles. Image quality loss will accumulate; after ten or so cycles the image may be noticeably worse than it was after one cycle. It's best to use a lossless format while manipulating an image, then convert to JPEG format when you are ready to file the image away.

The **-optimize** option to **cjpeg** is worth using when you are making a "final" version for posting or archiving. It's also a win when you are using low quality settings to make very small JPEG files; the percentage improvement is often a lot more than it is on larger files. (At present, **-optimize** mode is always selected when generating progressive JPEG files.)

ENVIRONMENT

JPEGMEM

If this environment variable is set, its value is the default memory limit. The value is specified as described for the **-maxmemory** switch. **JPEGMEM** overrides the default value specified when the program was compiled, and itself is overridden by an explicit **-maxmemory**.

SEE ALSO

djpeg(1), **jpegtran**(1), **rdjpgcom**(1), **wrjpgcom**(1)

ppm(5), **pgm**(5)

Wallace, Gregory K. "The JPEG Still Picture Compression Standard", Communications of the ACM, April 1991 (vol. 34, no. 4), pp. 30-44.

AUTHOR

Independent JPEG Group

BUGS

GIF input files are no longer supported, to avoid the Unisys LZW patent. (Conversion of GIF files to JPEG is usually a bad idea anyway.)

Not all variants of BMP and Targa file formats are supported.

The **-targa** switch is not a bug, it's a feature. (It would be a bug if the Targa format designers had not been clueless.)