

Package ‘scimetr’

March 16, 2026

Type Package

Title Analysis of Scientific Publication Data with R

Version 1.2.0

Date 2026-03-01

Description Tools for quantitative research in scientometrics and bibliometrics.

This package provides routines for importing bibliographic data from Clarivate Web of Science (<<https://www.webofscience.com/wos/>>) and performing bibliometric analysis.

Depends R (>= 4.1.0), graphics

Imports dplyr, tidyr, stringr, stringi, scales, ggplot2, rlang,
openxlsx

Suggests DT, rmarkdown, knitr

License GPL (>= 2)

URL <https://rubenfcasal.github.io/scimetr/>,
<https://github.com/rubenfcasal/scimetr/>

BugReports <https://github.com/rubenfcasal/scimetr/issues/>

Encoding UTF-8

VignetteBuilder knitr

LazyData true

RoxygenNote 7.3.2

NeedsCompilation no

Author Ruben Fernandez-Casal [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-5785-3739>>),
Borja Lafuente-Rego [aut] (ORCID:
<<https://orcid.org/0000-0002-2443-3084>>),
Maria Jose Lombardia [aut] (ORCID:
<<https://orcid.org/0000-0001-9452-9818>>),
Javier Tarrío-Saavedra [aut] (ORCID:
<<https://orcid.org/0000-0002-9584-127X>>),
Julian Costa-Bouzas [aut] (ORCID:

<<https://orcid.org/0000-0001-9760-9581>>),

Yesica Fernandez-Ramos [ctb],

Guillermo Lopez-Taboada [ctb]

Maintainer Ruben Fernandez-Casal <rubenfcasal@gmail.com>

Repository CRAN

Date/Publication 2026-03-16 20:00:02 UTC

Contents

| | |
|---------------------------|----|
| scimetr-package | 2 |
| add_jcr | 3 |
| dbjcr | 4 |
| db_bib | 4 |
| db_jcr | 6 |
| get_id_docs | 7 |
| get_jcr | 8 |
| import_wos | 9 |
| summary.wos.db | 10 |
| summary_year | 11 |
| wosdf | 13 |

Index **16**

| | |
|-----------------|--|
| scimetr-package | <i>scimetr: Analysis of Scientific Publication Data with R</i> |
|-----------------|--|

Description

Tools for quantitative research in scientometrics and bibliometrics. This package provides routines for importing bibliographic data from Clarivate Web of Science (<https://www.webofscience.com/wos/>) and performing bibliometric analysis. For more information visit <https://rubenfcasal.github.io/scimetr/articles/scimetr.html>.

Author(s)

Maintainer: Ruben Fernandez-Casal <rubenfcasal@gmail.com> ([ORCID](#))

Authors:

- Borja Lafuente-Rego <borjalrego@gmail.com> ([ORCID](#))
- Maria Jose Lombardia <maria.jose.lombardia@udc.es> ([ORCID](#))
- Javier Tarrio-Saavedra <javier.tarrio@udc.es> ([ORCID](#))
- Julian Costa-Bouzas <julian.costa.bouzas@udc.es> ([ORCID](#))

Other contributors:

- Yesica Fernandez-Ramos <yesica.ramos@udc.es> [contributor]
- Guillermo Lopez-Taboada <guillermo.lopez.taboada@udc.es> [contributor]

See Also

Useful links:

- <https://rubenfcasal.github.io/scimetr/>
- <https://github.com/rubenfcasal/scimetr/>
- Report bugs at <https://github.com/rubenfcasal/scimetr/issues/>

 add_jcr

Add JCR data to a bibliographic database

Description

Extends the bibliographic database by adding JCR metrics to sources, per year and WoS category.

Usage

```
add_jcr(db, jcrdb)
```

```
## S3 method for class 'wos.jcr'
plot(
  x,
  filter,
  plot = TRUE,
  all = FALSE,
  ask = plot && all && interactive(),
  ...
)
```

Arguments

| | |
|--------|--|
| db | a bibliographic database (a <code>wos.db</code> object; typically the output of the function <code>db_bib()</code>). |
| jcrdb | a JCR database (a <code>jcr.db</code> object; typically the output of the function <code>db_jcr()</code>). |
| x | a <code>wos.jcr</code> object. |
| filter | vector of document identifiers (usually a result of <code>get_id_docs()</code>). |
| plot | logical; if TRUE (default), the plots are drawn, otherwise only the ggplot2 object is (invisibly) returned. |
| all | logical; if TRUE, function <code>plot.wos.db()</code> is called (additional parameters ... are passed to this function), otherwise only a JCR metrics plot is generated. |
| ask | logical; if TRUE, the user is asked before each plot (see <code>par(ask=.)</code>). |
| ... | further arguments passed to or from other methods. |

Value

An S3 object of class `wos.jcr`. A `wos.db` object with additional components `JCRSour` and `JCRCatSour`.

See Also

[db_bib](#), [db_jcr](#).

dbjcr

Mathematics UDC 2018-2023 bibliographic database

Description

Bibliographic database with JCR metrics (a [wos.jcr](#) S3 object) corresponding to a WoS search by the Affiliation field of *Universidade da Coruña (UDC)* in the research area "Mathematics" during the years 2018–2023 (generated from [wosdf](#) data set, using the functions [db_bib](#), [db_jcr](#) and [add_jcr](#)).

Usage

```
dbjcr
```

Format

An object of class `wos.jcr` (inherits from `wos.db`) of length 22.

db_bib

Bibliographic data base creation

Description

`db_bib.wos.data()` converts a data.frame with WoS variables (as returned by [import_wos](#); see [wosdf](#)) into a relational database (a list of data.frames).

Usage

```
db_bib(data, ...)

## S3 method for class 'wos.data'
db_bib(data, label = "", progress = interactive(), verbose = FALSE, ...)

## S3 method for class 'wos.db'
print(x, ...)

## S3 method for class 'wos.db'
plot(
  x,
  filter,
  which = 1:3,
  plot = TRUE,
  warning = FALSE,
  ask = plot && (length(which) > 1) && interactive(),
  ...
)
```

Arguments

| | |
|----------|---|
| data | a data.frame with bibliographic data. |
| ... | further arguments passed to or from other methods. |
| label | character string describing the data. |
| progress | logical; if TRUE the progress is printed. |
| verbose | logical; if TRUE additional information is printed. |
| x | an object used to select a method. |
| filter | vector of document identifiers (usually a result of get_id_docs). |
| which | if a subset of the plots is required, specify a subset of the numbers 1:3. |
| plot | logical; if TRUE (default), the plots are drawn, otherwise only the list of <code>ggplot2</code> objects is (invisibly) returned. |
| warning | logical; if FALSE (default), warnings are ignored. |
| ask | logical; if TRUE, the user is asked before each plot (see par(ask=.)). |

Value

An S3 object of class `wos.db`. A list with the following components:

- Docs: document-level records (year, type, citations, identifiers).
- Authors and AutDoc: author dictionary and document-author links.
- OI and OIDoc: ORCID identifiers and their linkage to documents.
- RI and RIDoc: ResearcherID identifiers and their linkage to documents.
- Affiliations and AffDoc: affiliation dictionary and document links.
- Addresses and AddAutDoc: address and document-author-address links.
- Sources: document sources (journals, books, proceedings, ...).
- Categories, Areas, CatSour and AreaSour: thematic classifications and their linkage to sources.
- WSIndex and SourWSI: Web of Science indexes and their linkage to sources.
- Label and date: metadata that helps tracking the dataset identity over time.

This object has specialized [print](#) and [plot](#) methods.

See Also

[wosdf](#), [import_wos](#).
[summary.wos.db](#).
[plot.summary.wos.db](#), [plot.summary.year.wos](#)

Examples

```
db <- db_bib(wosdf)
print(db)
summary(db)
```

db_jcr

*Import JCR data from Web of Science (WoS)***Description**

Reads JCR data from excel files downloaded from WoS and generates a relational database (a list of data.frames). It is assumed that the file name format is *JCR_[WE]_[PY]*, where *[WE]* is the WoS index (SCIE, SSCI, ...) and *[PY]* the JCR year.

Usage

```
db_jcr(path = ".", files = dir(path, pattern = "*.xlsx"), verbose = TRUE)
```

Arguments

| | |
|---------|---|
| path | character; path to the directory containing the files. Defaults to the working directory. |
| files | character vector with the file names. Defaults to filenames in directory path with extension <i>.xlsx</i> . |
| verbose | logical; indicating whether the name of the file being processed is printed. Defaults to TRUE. |

Details

A subscription to Web of Science is required to download JCR data. For successful execution, Excel files must retain the original header fields from Clarivate exports: Title20, ISO_ABBREV, TITLE, ISSN, EISSN, ISSUES/YEAR, COUNTRY, LANGUAGE, 1ST_YR_PUB, categories, TOT_CITES, CITES_JCR_YR, CITES_JCR_YR1, CITES_JCR_YR2, IF_NUMERATOR, CITES_JCR_YR3, CITES_JCR_YR4, CITES_JCR_YR5, 5YR_IF_NUMERATOR, ITEMS_JCR_YR, ITEMS_JCR_YR1, ITEMS_JCR_YR2, IF_DENOMINATOR, ITEMS_JCR_YR3, ITEMS_JCR_YR4, ITEMS_JCR_YR5, 5YR_IF_DENOMINATOR, IMPACT_FACTOR, IMMEDIACY_INDEX, CITED_HALF_LIFE, 5YR_IMPACT_FACTOR, EIGENFACTOR, NORM_EIGENFACTOR, ARTL_INFLUENCE, FREQUENCY, PUBCODE, PUBLISHER_NAME, CATEGORY_CODE, CATEGORY_DESCRIPTION, CATEGORY_RANKING, QUARTILE_RANK, JIF_PERCENTILE.

Value

An S3 object of `class` `jcr.db`. A list with components: Sources, Categories, JCRSour and JCRCatSour.

See Also

[db_bib](#), [add_jcr](#).

| | |
|-------------|------------------------------|
| get_id_docs | <i>Get table identifiers</i> |
|-------------|------------------------------|

Description

Retrieve internal identifiers (entity keys) for the corresponding relational table (authors, sources, categories, areas, ...). Any field in the target table can be used as a condition, and multiple conditions are combined with & (only IDs for which all conditions evaluate to TRUE are returned). *Tidy evaluation* can be used to construct the logical expressions, see [dplyr::filter\(\)](#).

Usage

```
get_id_docs(  
  db,  
  ...,  
  id_sources,  
  id_authors,  
  id_addresses,  
  id_oi,  
  id_ri,  
  id_affiliations  
)  
  
get_id_authors(db, ...)  
  
get_id_addresses(db, ...)  
  
get_id_areas(db, ...)  
  
get_id_categories(db, ...)  
  
get_id_wsi(db, ...)  
  
get_id_sources(db, ..., id_categories, id_areas, id_wsi)  
  
get_id_oi(db, ...)  
  
get_id_ri(db, ...)  
  
get_id_affiliations(db, ...)
```

Arguments

| | |
|------------|--|
| db | Object of <code>class</code> <code>wos.db</code> , as returned by <code>db_bib</code> . |
| ... | Logical predicates. Multiple conditions are combined with & (see filter). |
| id_sources | optional; sources identifiers. |

| | |
|-----------------|---|
| id_authors | optional; author identifiers (values of db\$Authors\$ids). |
| id_addresses | optional; addresses identifiers. |
| id_oi | optional; ORCID identifiers or codes (values of db\$OI\$OI). |
| id_ri | optional; RI identifiers or codes (values of db\$RI\$RI). |
| id_affiliations | optional; affiliations identifiers or names (values of db\$Affiliations\$C3). |
| id_categories | optional; categories identifiers or names (values of db\$Categories\$WC) |
| id_areas | optional; research area identifiers or names (values of db\$Areas\$SC) |
| id_wsi | optional; WoS Index identifiers or names (values of db\$WSI\$WE) |

Value

An integer vector of identifiers. For instance, `get_id_docs` returns the document identifiers (values of the `db$Docs$idd` variable) corresponding to identifiers of authors, categories, areas, addresses and/or sources. Logical expressions defined in terms of the variables in `db$Docs` can also be used as arguments.

See Also

[db_bib](#), [filter](#).

| | |
|---------|------------------------|
| get_jcr | <i>Get JCR metrics</i> |
|---------|------------------------|

Description

`get_jcr()` combines document indexes with their source JCR metrics per year.

`get_jcr_cat()` combines document indexes with their source JCR metrics per year and WoS category.

Usage

```
get_jcr(db, filter)
```

```
get_jcr_cat(db, filter, best = TRUE)
```

Arguments

| | |
|--------|--|
| db | a bibliographic database with JCR information (a wos.jcr object; typically the output of the function add_jcr()). |
| filter | vector of document identifiers (usually a result of get_id_docs()). |
| best | logical; if TRUE (default), only the results for the WoS category with the best ranking for each document are returned. |

Value

A data.frame with document indexes and their source JCR metrics.

See Also

[add_jcr\(\)](#), [db_jcr\(\)](#), [db_bib\(\)](#).

Examples

```
head(get_jcr(dbjcr))
head(get_jcr_cat(dbjcr, best = TRUE))
```

import_wos

Import bibliographic data downloaded from Web of Science (WoS).

Description

Reads bibliography entries from UTF-8 encoded Tab-delimited files containing "Full Record and Cited References" (see [wosdf](#) and vignette [Downloading data from the Web of Science](#)).

Usage

```
import_wos(path = ".", pattern = "*.txt", all = TRUE, progress = NULL)
```

Arguments

| | |
|----------|---|
| path | character; path to the directory containing the files. |
| pattern | regular expression; only matching files will be loaded. Defaults to "*.txt". |
| all | logical; indicating whether sources without ISSN are included (TRUE) or not (FALSE) in the result. Defaults to TRUE. |
| progress | logical; indicating whether a progress bar should be displayed. Defaults to TRUE when R is used interactively and there is more than one file, and FALSE otherwise. |

Details

A subscription to Web of Science is required to download bibliometric data.

Value

A data.frame with rows corresponding to sources and columns to WoS variables.

See Also

[wosdf](#), [db_bib\(\)](#).

summary.wos.db

*Summaries of a bibliographic database***Description**

`summary()` methods for bibliometric databases.

Usage

```
## S3 method for class 'wos.db'
summary(object, filter, index = c("H", "G"), nmax = 10, ...)

## S3 method for class 'summary.wos.db'
print(x, ...)

author_metrics(db, id_authors)

## S3 method for class 'summary.wos.db'
plot(
  x,
  which = 1:5,
  pie = FALSE,
  others = !pie,
  accuracy = 0.1,
  plot = TRUE,
  ask = length(which) > 1 && interactive(),
  ...
)

## S3 method for class 'wos.jcr'
summary(object, filter, all = FALSE, ...)

## S3 method for class 'summary.wos.jcr'
print(x, digits = 2, all = TRUE, ...)

## S3 method for class 'summary.wos.jcr'
plot(x, plot = TRUE, all = FALSE, ask = plot && all && interactive(), ...)
```

Arguments

| | |
|--------|---|
| object | an object for which a summary is desired. |
| filter | vector of document identifiers (optional, usually a result of <code>get_id_docs()</code>). |
| index | citation indexes. |
| nmax | number of top levels. |
| ... | further arguments passed to or from other methods. |

| | |
|------------|--|
| x | an object used to select a method. |
| db | Object of <code>class</code> <code>wos.db</code> , as returned by <code>db_bib</code> . |
| id_authors | optional; author identifiers |
| which | if a subset of the plots is required, specify a subset of the numbers 1:5. |
| pie | logical; if TRUE, pie charts are drawn. |
| others | logical; if FALSE, only nmax top levels categories are shown. |
| accuracy | numerical scalar; see <code>label_number(accuracy=.)</code> . |
| plot | logical; if TRUE (default), the plots are drawn, otherwise only the list of <code>ggplot2</code> objects is (invisibly) returned. |
| ask | logical; if TRUE, the user is asked before each plot, see <code>par(ask=.)</code> . |
| all | logical; if TRUE, the corresponding <code>wos.db</code> method is called (additional parameters ... are passed to it), otherwise only results of JCR metrics are returned. |
| digits | minimal number of significant digits, see <code>print.default</code> . |

Value

A list of summary statistics (an object of class `summary.wos.db` and/or `summary.wos.jcr`), which has specialized `print()` and `plot()` methods.

See Also

`db_bib()`, `add_jcr()`.

Examples

```
# Bibliographic database
db <- db_bib(wosdf)
summary(db)
# Bibliographic database with JCR metrics
summary(dbjcr)
```

summary_year

Summaries per year

Description

The `summary_year` methods return summaries by year of a bibliometric database.

Usage

```
summary_year(object, ...)

## S3 method for class 'wos.db'
summary_year(object, filter, ...)

## S3 method for class 'summary.year.wos'
print(x, ...)

## S3 method for class 'summary.year.wos'
plot(
  x,
  which = 1:3,
  boxplot = FALSE,
  plot = TRUE,
  ask = plot && length(which) > 1 && interactive(),
  ...
)

## S3 method for class 'wos.jcr'
summary_year(object, filter, all = FALSE, ...)

## S3 method for class 'summary.year.jcr'
print(x, digits = 3, all = TRUE, ...)

## S3 method for class 'summary.year.jcr'
plot(x, plot = TRUE, all = FALSE, ask = plot && interactive(), ...)
```

Arguments

| | |
|---------|--|
| object | an object for which a summary is desired. |
| ... | further arguments passed to or from other methods. |
| filter | vector of document identifiers (optional, usually a result of get_id_docs). |
| x | an object used to select a method. |
| which | if a subset of the plots is required, specify a subset of the numbers 1:3. |
| boxplot | logical; if TRUE, boxplots are drawn (for plots from 2 to 3). |
| plot | logical; if TRUE (default), the plots are drawn, otherwise only the list of <code>ggplot2</code> objects is (invisibly) returned. |
| ask | logical; if TRUE, the user is asked before each plot, see <code>par(ask=.)</code> . |
| all | logical; if TRUE, the corresponding <code>wos.db</code> method is called (additional parameters ... are passed to it), otherwise only results of JCR metrics are returned. |
| digits | minimal number of <i>significant</i> digits, see print.default . |

Value

A list of summary statistics (an object of class `summary.year.wos` and/or `summary.year.jcr`), which has specialized `print()` and `plot()` methods.

See Also

[db_bib\(\)](#), [add_jcr\(\)](#).

Examples

```
# Bibliographic database
db <- db_bib(wosdf)
summary_year(db)
# Bibliographic database with JCR metrics
summary_year(dbjcr)
```

wosdf

Mathematics UDC WoS Core Collection 2018-2023 data

Description

The data set consists of 293 publications corresponding to a WoS search by the Affiliation field of *Universidade da Coruña (UDC)* (Affiliation: OG = Universidade da Coruna) in the research area "Mathematics" (SC = Mathematics), indexed in the Web of Science Core Collection:

- Science Citation Index Expanded (SCI-EXPANDED).
- Social Sciences Citation Index (SSCI).
- Arts & Humanities Citation Index (A&HCI).

in the years 2018-2023 (generated using the [import_wos](#) function).

Usage

```
wosdf
```

Format

A data frame with 293 rows and 48 columns:

PT Publication Type
AU Author
AF Author Full Name
TI Article Title
SO Source Title
SE Book Series Title
BS Book Series Subtitle
LA Language
DT Document Type
C1 Address
C3 Affiliation

RI Researcher Ids
OI ORCID
NR Cited Reference Count
TC Times Cited, WoS Core
Z9 Times Cited, All Databases
U1 180 Day Usage Count
U2 Since 2013 Usage Count
PU Publisher
PI Publisher City
PA Publisher Address
SN ISSN
EI eISSN
BN ISBN
J9 Journal Abbreviation
JI Journal ISO Abbreviation
PD Publication Date
PY Publication Year
VL Volume
IS Issue
PN Part Number
SU Supplement
SI Special Issue
MA Meeting Abstract
BP Start Page
EP End Page
AR Article Number
DI DOI
D2 Book DOI
EA Early Access Date
PG Number of Pages
WC WoS Category
WE Web of Science Index
SC Research Area
HC Highly Cited Status
HP Hot Paper Status
DA Date of Export
UT Unique WOS ID

Source

Clarivate Web of Science: <https://www.webofscience.com/wos/>.

See Also

[import_wos](#), [db_bib](#)

Index

- * **datasets**
 - dbjcr, 4
 - wosdf, 13
- add_jcr, 3, 4, 6
- add_jcr(), 8, 9, 11, 13
- author_metrics (summary.wos.db), 10
- class, 3, 5–7, 11
- db_bib, 4, 4, 6–8, 11, 15
- db_bib(), 3, 9, 11, 13
- db_jcr, 4, 6
- db_jcr(), 3, 9
- dbjcr, 4
- dplyr::filter(), 7
- filter, 7, 8
- get_id_addresses (get_id_docs), 7
- get_id_affiliations (get_id_docs), 7
- get_id_areas (get_id_docs), 7
- get_id_authors (get_id_docs), 7
- get_id_categories (get_id_docs), 7
- get_id_docs, 5, 7, 12
- get_id_docs(), 3, 8, 10
- get_id_oi (get_id_docs), 7
- get_id_ri (get_id_docs), 7
- get_id_sources (get_id_docs), 7
- get_id_wsi (get_id_docs), 7
- get_jcr, 8
- get_jcr_cat (get_jcr), 8
- import_wos, 4, 5, 9, 13, 15
- jcr.db, 3
- jcr.db-class (db_jcr), 6
- label_number, 11
- par, 3, 5, 11, 12
- plot, 5
- plot(), 11, 12
- plot.summary.wos.db, 5
- plot.summary.wos.db (summary.wos.db), 10
- plot.summary.wos.jcr (summary.wos.db), 10
- plot.summary.year.jcr (summary_year), 11
- plot.summary.year.wos, 5
- plot.summary.year.wos (summary_year), 11
- plot.wos.db (db_bib), 4
- plot.wos.db(), 3
- plot.wos.jcr (add_jcr), 3
- print, 5
- print(), 11, 12
- print.default, 11, 12
- print.summary.wos.db (summary.wos.db), 10
- print.summary.wos.jcr (summary.wos.db), 10
- print.summary.year.jcr (summary_year), 11
- print.summary.year.wos (summary_year), 11
- print.wos.db (db_bib), 4
- scimetr (scimetr-package), 2
- scimetr-package, 2
- summary(), 10
- summary.wos.db, 5, 10
- summary.wos.jcr (summary.wos.db), 10
- summary_year, 11
- wos.db, 3, 11, 12
- wos.db-class (db_bib), 4
- wos.jcr, 3, 4, 8
- wos.jcr-class (add_jcr), 3
- wosdf, 4, 5, 9, 13